



## V-AX18



Finger



RFID



Battery  
(Optional)



LAN



USB



Access Control

### Fingerprint Time Attendance and Access Control

- Fingerprint Capacity : 3000
- Card Capacity : 3000
- Log Capacity : 1,00,000
- CPU : Industrial High Speed CPU
- Comm. : TCP/IP, Rs485, USB Host & Client
- Push Data : Yes
- Keypad : Feather Touch Keypad
- LCD : 2.8" Color Screen
- Verification Speed < 1 Sec
- Fingerprint Image Display : YES
- Memory : 512MB
- Sensor : 500 DPI Optical Sensor  
(Touch Active Sensor)
- FRR : 0.001%
- FAR : 0.00001%
- SSR : Yes
- Relay : Yes
- Support Exit Reader : V-R12, Wiegand Reader,  
Push Button, Remote, No Touch
- Door Switch, Door Sensor, Tamper Alarm
- Self-defined Status : Yes
- Built-in backup battery : Optional
- Wiegand input/output : Yes
- Optional : Mifare Card
- Access Groups & Time Schedules : 16 Groups,  
32 Time Zones, Anti Passback (With Counter)
- Power : DC 12V, 2Amp
- Temperature : -20°C ~ 50°C
- Dimensions(WxHxD) : 83.9 x 204.9 x 31mm
- Software : Desktop, Web, Cloud

\* Model No : **V-AX18+B** (With Inbuilt Battery Backup)