



XsPoint C1

Highly reliable and secure
Bluetooth enabled multi tag
contactless reader.

Part Number	XP-C1
Frequency	125KHz, ASK, 13.56MHz, ISO/IEC 14443A
Output Interface	Wiegand 26-128 Bits
Aux. Interface	RS232 serial ASCII, 19200, N, 8, 1 / RS485 (Secure OSDP) Selectable
Read Range	Up to 5cm
Support Tags	EM4100, TK4100, JH4101, EM4101, Mifare Classic 1K/4K, Ultralight, Desfire, Mifare Plus, Smart Card
Visual Indication	Tri Color LED
Green LED Control	Active low input to control the Green LED
Red LED Control	Active low input to control the red LED
Buzzer Control	Active low input to control the buzzer
Tamper Output	Open Collector Active Low
Configuration	CSN & Sector Read Mode, Configurable through master Card for Mifare 1K/4K
BLE	BLE 4.0
Color	Black
Input Voltage	8-16V DC
Input Current	66mA Max @12V DC
Housing	UL94 Polycarbonate
Protection	IP65
Operating Temp.	-10 to 55°C
Weight	52 gram
Dimension (mm)	H 100 x W 44.70 X D 16.70

Technical specifications may be changed from time to time without any prior notice due to continuous enhancements in the product.



Head Office

Spectra Technovision (India) Pvt. Ltd.
707-708-709, Venus Atlantis Corporate Park,
Prahlanagar, Ahmedabad-380015 India.

+91 79 44111222 ✉ sales@spectra-vision.com

Branch Offices

Mumbai ☎ +91 22 44111222
Bangalore ☎ +91 80 44111222

