

Instruction

The DNAKE S215 enables you to make the video call with apartment entrance door, and open the door remotely from indoor monitor or mobile APP. It also makes an easy integration with SIP devices and lift control system.

Key Features

- Induction loop for hearing impaired
- Braille dot for visually impaired
- 3 output relays for door lock
- Tamper alarm

Physical

- System: Linux
- Front Panel: Aluminum
- Button: Mechanical
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 9 W
- Camera: 2MP, CMOS
- IR Sensor: Support
- Wiegand Port: Support
- Ethernet Ports: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: IC card (13.56MHz), ID card(125kHz), PIN code, NFC
- Reset button: 1
- RS485 Port: 1
- Relay Out: 3
- Exit Button / Door Magnetic : 4
- IP / IK Rating: IP65 / IK08
- Installation: Flush mounting & Surface mounting
- Flush mounting DIM: 295 x 133 x 63.5 mm
- Surface mounting DIM: 295 x 133 x 42.7 mm
- Working Temperature: -40°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

DNAKE S215



Datasheet

Display

- Display: 4.3-inch TFT LCD
- Resolution: 480x272

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing angle: 110° (H) / 67° (V) / 127° (D)
- Max. Image Transfer Rate: 720p – 30fps
- Light Compensation: LED white light

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE S215
(Power adapter not included)
 - Surface Mounting Box
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 10 pcs
- N.W/PCS: 1.53 kg
- G.W/CTN: 20 kg
- Giftbox Size: 362 x 170 x 100 mm
- Carton Size: 480 x 410 x 435 mm

