



XsPoint Plus

Highly reliable and secure
contactless card reader for
access control solutions

XsPoint Plus

EM/Mifare/BLE/QR Code Reader

TECHNICAL SPECIFICATIONS

Part Number	XPPlus-C1	XPPlus-C2
Frequency	Dual Frequency 125KHz, ASK & 13.56MHz	
Weigand Output	One Port, Wiegand 26-128 Bits configurable or Clock-and-Data	
OSDP	One RS485 port supporting secure OSDP protocol	
RS232C	One RS232C port for data over serial interface, ASCII 19200 baudrate N,8,1	
USB	USB 2.0 serial port	
Card Read Range	Up to 7cm	
Support Tags	EM4100, TK4100, JH4101, EM4101, Mifare Classic 1K/4K, Ultralight, Desfire, Mifare Plus smart card	
Visual Indication	Tri Color LED. Red, Green and White	
Green LED Control	Active low input to control the green LED	
Red LED Control	Active low input to control the red LED	
Buzzer Control	Active low input to control the buzzer	
Tamper Output	Open Collector Active Low	
Configuration	CSN & Sector Read Mode, Configurable through master card for Mifare 1K/4K	
BLE	Yes	Yes
QR Code Reader	No	Yes
QR Resolution	-	648x488 pixel, 0.10mm
QR Scan Angle	-	360 degree
Housing	ABS, Flame retardant	
Color	Black	
Input Voltage	8-16V DC	
Input Current	90mA MAX @12V DC	
Ingress Protection	IP66	
Operating Temp.	-10 to 55°C	
Weight	100 gram (Approx.)	
Dimension (mm)	L 92 x W 92 X D 25.5	

Technical specifications may be changed from time to time without any prior notice due to continuous enhancements in the product.



Head Office

Spectra Technovision (India) Pvt. Ltd.
707-708-709, Venus Atlantis Corporate Park,
Prahlanagar, Ahmedabad-380015 India.

+91 79 44111222 ✉ sales@spectra-vision.com

Branch Offices

Mumbai ☎ +91 22 44111222

Bangalore ☎ +91 80 44111222

Gurgaon ☎ +91 124 4386354

