

HuAi

Ai Dynamic face recognition reader for attendance and access control solution

BV-2210



Main features:-

5000
50,000
(optional)

Face
Capacity

5
Users

Single/Multi user
recognition

0.5~2.5
meters

Recognition
Distance

< .03s

Recognition
Speed

WDR

200W Colorful
WDR

4.3
inches

Screen
Display



Touch
Screen



Multi
Language



Access
Control

200W

Infrared Live
Camera

272*480

HD
Screen

99.70%

Face Recognition
Accuracy



Mask
Detection



1.2G Dual Core
ARM Cortex A7



WiFi
Ethernet



Specifications

Product name Ai Dynamic Face recognition Attendance & Access Control terminal
Screen 4.3" HD 272x480 Capacitive Touch Screen

Keypad Touch Keypad
Operation system LINUX 3.10

CPU,NPU 1.2G Dual core ARM CortexA7, 600G(0.6T)
RAM 256MB DDR3

ROM eMMC Flash 4GB
Binocular camera 200W colourful WDR+ 200W infrared live camera

Face capacity 5,000 (50,000 optional)
Card Capacity 5,000 (50,000 optional)

Log capacity 500,000
Face Recognition Accuracy 99.70%

Recognition speed <0.5 sec, support single & multi users at same time (upto 5users)
Recognition distance 0.5 - 2.5 meters (0.5 - 1 meters with live face recognition on)

WDR Support face recognition under strong/dark light and backlight
USB USB 2.0, supports import and export of data

Powersupply DC12V
Communication TCP/IP, WiFi, Weigand 26/34 output, Input

Multi language English, Arabic, Spanish, French, Italian, Japanese, Korean
Working Voltage DC 12V

Dimension 187.5 x 87.5 x 26mm
Installation Wall Mount

Working Temperature -15 to +45 degree Celsius
Working Humidity 20% to 90%

HuAi

11-345, Ground floor, The Centre,
99 Queens Road Central, Hong Kong.