

# HuAi

**BV 2310 - face recognition, fingerprint & RFID card reader for attendance and access control**



5000



10,000



15,000



5 users



4.3" display




Dual Camera



Wide camera



Wifi/TCP IP



Dual Core



Live Face



# Specifications

<b>Product name</b>	<b>WDR Ai Dynamic Face recognition Attendance &amp; Access Control terminal</b>
<b>Screen</b>	<b>4.3" Touch Screen, HD 1280*720</b>
<b>Keypad</b>	<b>Touch Key</b>
<b>Operation system</b>	<b>LINUX 3.10</b>
<b>CPU,NPU</b>	<b>1.2G Dual core ARM CortexA7, 600G(0.6T)</b>
<b>RAM</b>	<b>256MB DDR3</b>
<b>ROM</b>	<b>4G EMMC</b>
<b>Binocular camera</b>	<b>Real sensor 1/2.9 inch 2MP WDR camera, Sensor 1/5 inch 2mp Live Camera</b>
<b>Face capacity</b>	<b>5,000 faces (20,000 optional)</b>
<b>Fingerprint Capacity</b>	<b>10,000 fingerprints (50,000 optional)</b>
<b>RFID card capacity</b>	<b>15,000 cards (50,000 optional)</b>
<b>Logs</b>	<b>500,000</b>
<b>Recognition speed</b>	<b>&lt;0.5 sec, support single &amp; multi users at same time (upto 5users)</b>
<b>Recognition distance</b>	<b>0.5 - 2.5 meters (0.5 - 1 meters with live face recognition on)</b>
<b>WDR</b>	<b>Support face recognition under strong/dark light and backlight</b>
<b>USB</b>	<b>USB 2.0, supports import and export of data</b>
<b>Powersupply</b>	<b>DC12V</b>
<b>Communication</b>	<b>TCP/IP, WiFi, Weigand 26/34 output, Input</b>
<b>Multi language</b>	<b>English, Spanish, French, Italian, Japanese, Korean</b>
<b>QR Code</b>	<b>Will Support</b>
<b>Dimension</b>	<b>155 x 25 x 155mm</b>
<b>Installation</b>	<b>Wall Mount</b>
<b>Working Temperature</b>	<b>-15 to +45 degree Celsius</b>
<b>Working Humidity</b>	<b>20% to 90%</b>

# HuAi

11-345, Ground floor, The Centre,  
99 Queens Road Central, Hong Kong.

\*Technical specifications may change from time to time without prior notice due to continuous enhancements in the product.